UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/528,508	10/11/2005	Teruya Maeda	450100-04781	4361
7590 10/18/2007 William S Frommer Frommer Lawrence & Haug			EXAMINER	
			HU, RUI MENG	
745 Fifth Avenue New York, NY 10151			ART UNIT	PAPER NUMBER
			2618	
	•		MAIL DATE	DELIVERY MODE
	•	·	10/18/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/528,508	MAEDA, TERUYA
Office Action Summary	Examiner	Art Unit
	RuiMeng Hu	2618
The MAILING DATE of this communicati Period for Reply	on appears on the cover sheet w	ith the correspondence address
A SHORTENED STATUTORY PERIOD FOR I WHICHEVER IS LONGER, FROM THE MAILI - Extensions of time may be available under the provisions of 37 after SIX (6) MONTHS from the mailing date of this communica - If NO period for reply is specified above, the maximum statutory - Failure to reply within the set or extended period for reply will, be Any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	NG DATE OF THIS COMMUNION CFR 1.136(a). In no event, however, may a lition. y period will apply and will expire SIX (6) MON y statute, cause the application to become AE	CATION. reply be timely filed NTHS from the mailing date of this communication. RANDONED (35 U.S.C. § 133).
Status		
 1) Responsive to communication(s) filed or 2a) This action is FINAL. 2b) Since this application is in condition for a closed in accordance with the practice u 	This action is non-final. Allowance except for formal matt	
Disposition of Claims		
4) Claim(s) 1-21 is/are pending in the application Papers	ithdrawn from consideration. and/or election requirement.	
9) The specification is objected to by the Ex 10) The drawing(s) filed on is/are: a) Applicant may not request that any objection Replacement drawing sheet(s) including the 11) The oath or declaration is objected to by	☐ accepted or b)☐ objected to to the drawing(s) be held in abeyar correction is required if the drawing	nce. See 37 CFR 1.85(a). n(s) is objected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for f a) All b) Some * c) None of: 1. Certified copies of the priority doc 2. Certified copies of the priority doc 3. Copies of the certified copies of the application from the International I * See the attached detailed Office action for	uments have been received. uments have been received in A e priority documents have been Bureau (PCT Rule 17.2(a)).	Application No received in this National Stage
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-93) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	48) Paper No(Summary (PTO-413) s)/Mail Date nformal Patent Application

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed on 07/30/2007 have been fully considered but they are not persuasive.

Applicant argues that the prior art reference Yokogawa et al. (JP 2000-232458) fails to disclose the limitation specifically the emphasized limitation "wherein said wireless communication apparatus for the base station performs scan processing of inputs of said antenna bodies and waits for receiving data, except for the time of making the wireless transmission."

Yokogawa et al. clearly disclose a conventional embodiment (see paragraphs 8, 9 and 12) wherein a wireless communication apparatus for the base station performs scan processing of inputs of antenna sector units and waits for receiving data (paragraphs 8 and 9, the key station establishes communication links between the child offices 2a-2c, specifically establishing the specific antenna sector unit of the key station for the communication link with each child offices 2a-2c and the establishment is updated timely), except for the time of making the wireless transmission (paragraph 12, after the communication links are established (to the child offices 2a-2c which the key station has already managed), the data communication are performed between the key station and the child offices using the already managed antenna sector units about the child offices (last sentence of paragraph 12), accordingly the scan processing of the key station is <u>not</u> performed during data communication (the time of making the wireless transmission)).

Application/Control Number: 10/528,508 Page 3

Art Unit: 2618

Response to Amendment

Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:
 - 1. Determining the scope and contents of the prior art.
 - 2. Ascertaining the differences between the prior art and the claims at issue.
 - 3. Resolving the level of ordinary skill in the pertinent art.
 - Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 4. Claims 1-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yokogawa et al. (JP 2000-232458).

Consider **claim 1**, Yokogawa et al. clearly disclose a system for making wireless communication processing between a wireless base station (the key station) and an arbitrary wireless terminal apparatus (child offices 2a-2c), said system comprising: a wireless communication apparatus for a base station (the key station), the apparatus including a plurality of antenna bodies each having a directional pattern in a predetermined direction (paragraph 0030, each antenna unit has directivity of 30 degrees, which associated with the field (service area)); and a wireless terminal apparatus, to become a communication target (child offices 2a-2c), that is capable of

the child offices 2a-2c).

station) for the base station (paragraph 0004, the key station holding many child offices 2a-2c), wherein said wireless communication apparatus for the base station performs: identification processing of the communication-targeted wireless terminal apparatus (child offices 2a-2c) located within a communication area of each of the directional patterns of said antenna bodies regularly or irregularly (paragraph 0008, child offices 2a-2c concerned exist in the subordinate (field which can be communicated) of a directional antenna); storage processing of a correspondence relationship between said communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 9, drawing 9, stored table stores each child office's ID and its assigned antenna); and at the time of making wireless communication, selection processing of the antenna body which corresponds to the pertinent wireless terminal apparatus based on the storage processing (paragraph 0012, data communication to the child offices 2a-2c using the already managed (stored) antenna (sector unit) about

Yokogawa et al. clearly disclose a conventional embodiment (see paragraphs 8, 9 and 12) wherein a wireless communication apparatus for the base station performs scan processing of inputs of antenna sector units and waits for receiving data (paragraphs 8 and 9, the key station establishes communication links between the child offices 2a-2c, specifically establishing the specific antenna sector unit of the key station for the communication link with each child offices 2a-2c and the establishment is updated timely), except for the time of making the wireless transmission (paragraph 12,

Art Unit: 2618

after the communication links are established (to the child offices 2a-2c which the key station has already managed), the data communication are performed between the key station and the child offices using the already managed antenna sector units about the child offices (last sentence of paragraph 12), accordingly the scan processing of the key station is <u>not</u> performed during data communication (the time of making the wireless transmission)).

Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the selection techniques taught by Yokogawa et al. into the art of Yokogawa et al. as to include the conventional embodiment as disclosed by Yokogawa et al. as a further embodiment.

Consider claim 2, as applied to claim 1 above, Yokogawa et al. as modified clearly disclose wherein said wireless communication apparatus for the base station at least comprises: a plurality of antenna bodies each having a directional pattern in a predetermined direction (paragraph 0030, each antenna unit has directivity of 30 degrees, which associated with the field (service area)); and a controller for allowing identifying the communication-targeted wireless terminal apparatus (child offices 2a-2c) located within the communication area (the subordinate or field of service area) created by each of the directional patterns of said antenna bodies (paragraph 0030), and recognizing the correspondence relationship between the pertinent communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 0009, drawing 9), wherein said controller performs: at the time of making wireless communication, selection processing of the antenna body which

corresponds to the pertinent wireless terminal apparatus (child offices 2a-2c), and communication processing with the wireless terminal apparatus (child offices 2a-2c) located within the communication area created by the pertinent directional pattern, using said selected antenna body (drawing 9, paragraph 0012, data communication to the child offices 2a-2c using the already managed (stored) antenna (sector unit) about the child offices 2a-2c).

Consider claim 3, as applied to claim 1 above, Yokogawa et al. as modified clearly disclose wherein said communication-targeted wireless terminal apparatus (child offices 2a-2c) is located within the communication area created by the predetermined directional pattern of said wireless communication apparatus (the key station) for the base station (paragraph 0008), or said communication-targeted wireless terminal apparatus (child offices 2a-2c) moves between the communication areas of these pertinent directional patterns (paragraph 0019).

Consider claim 4, as applied to claim 1 above, Yokogawa et al. as modified clearly disclose wherein said wireless communication apparatus for the base station comprises storing means (stored table) for storing antenna selection information indicative of the correspondence relationship between said communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 0009, drawing 9).

Consider claim 5, as applied to claim 4 above, Yokogawa et al. as modified clearly disclose wherein said wireless communication apparatus performs a memory

Art Unit: 2618

control over said storing means to update said antenna selection information (paragraph 0053).

Consider claim 6, as applied to claim 1 above, Yokogawa et al. as modified clearly disclose wherein said wireless communication apparatus regularly or irregularly transmits data (confirmation-of-receipt signal) for confirming that said communication-targeted wireless terminal apparatus (child offices 2a-2c) is present in the communication area to the wireless terminal apparatus (paragraph 0022).

Consider claim 7, as applied to claim 1 above, Yokogawa et al. as modified clearly disclose wherein said wireless communication apparatus for the base station comprises at least two antenna bodies having different directional patterns from each other (paragraph 0030), and wherein said wireless communication apparatus (key station) transmits a reference signal to the communication-targeted wireless terminal apparatus (child offices 2a-2c) within the communication area created by the pertinent directional pattern from both of said antenna bodies alternately (paragraphs 0022, 0023, consider a child office travels between communication areas created by the pertinent directional pattern, and the stored table (drawing 9) gets reset, different antenna units would be used).

Consider claim 8, as applied to claim 1 above, Yokogawa et al. as modified clearly disclose wherein said wireless communication apparatus (key station) for the base station receives the data using the antenna body that receives the strongest radio wave from said communication-targeted wireless terminal apparatus (paragraph 12,

Art Unit: 2618

using the already managed antenna unit (desired antenna unit) about the child offices 2a-2c).

Consider claim 9, Yokogawa et al. clearly disclose a wireless communication apparatus (the key station) for arbitrarily making wireless communication with a wireless terminal apparatus (child offices 2a-2c), to become a communication target, said apparatus comprising (paragraph 0007): a plurality of antenna bodies each having a directional pattern in a predetermined direction (paragraph 0030, each antenna unit has directivity of 30 degrees, which associated with the field (service area)); and a controller (paragraph 0008, the key station) for allowing identifying a communication-targeted wireless terminal apparatus (child offices 2a-2c) located within a communication area created by each of the directional patterns of said antenna bodies, and recognizing a correspondence relationship between the pertinent communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 0009, drawing 9), wherein said controller performs: at the time of making wireless communication, selection processing of the antenna body which corresponds to the pertinent wireless terminal apparatus (each of child offices 2a-2c associating with a directional antenna according to the stored table (drawing 9); and communication processing with the wireless terminal apparatus located within the pertinent directivity using said selected antenna body (paragraph 0012, data communication to the child offices 2a-2c using the already managed (stored) antenna (sector unit) about the child offices 2a-2c).

Yokogawa et al. clearly disclose a conventional embodiment (see paragraphs 8, 9 and 12) wherein the controller of the base station performs scan processing of inputs of antenna sector units and waits for receiving data (paragraphs 8 and 9, the key station establishes communication links between the child offices 2a-2c, specifically establishing the specific antenna sector unit of the key station for the communication link with each child offices 2a-2c and the establishment is updated timely), except for the time of making the wireless transmission (paragraph 12, after the communication links are established (to the child offices 2a-2c which the key station has already managed), the data communication are performed between the key station and the child offices using the already managed antenna sector units about the child offices (last sentence of paragraph 12), accordingly the scan processing of the key station is not performed during data communication (the time of making the wireless transmission)).

Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the selection techniques taught by Yokogawa et al. into the art of Yokogawa et al. as to include the conventional embodiment as disclosed by Yokogawa et al. as a further embodiment.

Consider claim 10, as applied to claim 9 above, Yokogawa et al. as modified clearly disclose storing means for storing antenna selection information indicative of the correspondence relationship between said communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 0009, drawing 9).

Consider **claim 11, as applied to claim 10 above**, Yokogawa et al. as modified clearly disclose wherein said controller performs a memory control over said storing means to update said antenna selection information (paragraph 0053).

Consider claim 12, as applied to claim 9 above, Yokogawa et al. as modified clearly disclose wherein said controller regularly or irregularly transmits data for confirming that said communication targeted wireless terminal apparatus is present in the communication area to the wireless terminal apparatus (paragraph 0022).

Consider claim 13, as applied to claim 9 above, Yokogawa et al. as modified clearly disclose comprising said antenna bodies of at least two having different directional patterns from each other (paragraph 0030), wherein the controller allows transmitting a reference signal to the communication-targeted wireless terminal apparatus (child offices 2a-2c) within the pertinent directivity from both of said antenna bodies alternately (paragraphs 0022, 0023, consider a child office travels between communication areas created by the pertinent directional pattern, and the stored table (drawing 9) gets reset, different antenna units would be used).

Consider **claim 14**, **as applied to claim 9 above**, Yokogawa et al. as modified clearly disclose wherein the controller (the key station) receives the data using the antenna body that receives the strongest radio wave (the most desired antenna) from said communication-targeted wireless terminal apparatus (paragraph 12, using the already managed antenna unit (desired antenna unit) about the child offices 2a-2c).

Consider **claim 15**, Yokogawa et al. clearly disclose a method for arbitrarily making wireless communication with a wireless terminal apparatus (child offices 2a-2c),

Page 11

Art Unit: 2618

to become a communication-target, said method comprising the steps of: providing a plurality of antenna bodies each having a directional pattern in a predetermined direction to a wireless communication apparatus (the key station) for a base station (paragraph 0030, each antenna unit has directivity of 30 degrees, which associated with the field (service area)), and preparing the communication-targeted wireless terminal apparatus (child offices 2a-2c) which is capable of wireless communication within a communication area (field of service area or subordinate) created by the arbitrary directional pattern; in said wireless communication apparatus (the key station) for the base station, regularly or irregularly identifying the communication-targeted wireless terminal apparatus located within a communication area created by each of the directional patterns of said antenna bodies (paragraph 0008); storing a correspondence relationship between said identified communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 0009, drawing 9); at the time of making wireless communication, selecting the antenna body which corresponds to the pertinent wireless terminal apparatus (according to the stored table drawing 9, each of child offices 2a-2c associating with a desired antenna); and performing communication processing with the wireless terminal apparatus located within the pertinent directivity using said selected antenna body (paragraph 0012, data communication to the child offices 2a-2c using the already managed (stored) antenna (sector unit) about the child offices 2a-2c).

Yokogawa et al. clearly disclose a conventional embodiment (see paragraphs 8, 9 and 12) wherein the base station performs scan processing of inputs of antenna

2212

Art Unit: 2618

sector units and waits for receiving data (paragraphs 8 and 9, the key station establishes communication links between the child offices 2a-2c, specifically establishing the specific antenna sector unit of the key station for the communication link with each child offices 2a-2c and the establishment is updated timely), except for the time of making the wireless transmission (paragraph 12, after the communication links are established (to the child offices 2a-2c which the key station has already managed), the data communication are performed between the key station and the child offices using the already managed antenna sector units about the child offices (last sentence of paragraph 12), accordingly the scan processing of the key station is not performed during data communication (the time of making the wireless transmission)).

Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the selection techniques taught by Yokogawa et al. into the art of Yokogawa et al. as to include the conventional embodiment as disclosed by Yokogawa et al. as a further embodiment.

Consider claim 16, as applied to claim 15 above, Yokogawa et al. as modified clearly disclose the steps of locating (paragraphs 0007, 0008) said communication-targeted wireless terminal apparatus (child offices 2a-2c) within the communication area (field of service area or subordinate) created by the predetermined directional pattern of said wireless communication apparatus for a base station (paragraph 0030), or allowing said communication-targeted wireless terminal apparatus (child offices 2a-2c) to move between the communication areas (subordinates) created by these directional patterns (paragraph 0019).

Consider claim 17, as applied to claim 15 above, Yokogawa et al. as modified clearly disclose the step of creating antenna selection information indicative of the correspondence relationship between said communication-targeted wireless terminal apparatus (child offices 2a-2c) and each of said antenna bodies (paragraph 0009, drawing 9).

Consider **claim 18**, **as applied to claim 17 above**, Yokogawa et al. as modified clearly disclose the step of updating said antenna selection information (paragraph 0053).

Consider **claim 19**, **as applied to claim 15 above**, Yokogawa et al. as modified clearly disclose the step of regularly or irregularly transmitting data for confirming that said communication-targeted wireless terminal apparatus is present in the communication area to the wireless terminal apparatus (paragraph 0022).

Consider claim 20, as applied to claim 15 above, Yokogawa et al. as modified clearly disclose the steps of: providing said antenna bodies of at least two having different directivities from each other (paragraph 0030); and transmitting a reference signal through both of said antenna bodies to the communication-targeted wireless terminal apparatus (child offices 2a-2c) within the pertinent directivity alternately (paragraphs 0022, 0023, consider a child office travels between communication areas created by the pertinent directional pattern, and the stored table (drawing 9) gets reset, different antenna units would be used).

Consider claim 21, as applied to claim 15 above, Yokogawa et al. as modified clearly disclose the steps of: receiving the data using the antenna body that receives the

strongest radio wave (most desired antenna) from said communication-targeted wireless terminal apparatus (paragraph 0012, using the already managed antenna unit (desired antenna unit) about the child offices 2a-2c).

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any response to this Office Action should be faxed to (571) 273-8300 or mailed

to:

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Hand-delivered responses should be brought to

Application/Control Number: 10/528,508 Page 15

Art Unit: 2618

Customer Service Window Randolph Building
401 Dulany Street
Alexandria, VA 22314

Any inquiry concerning this communication or earlier communications from the examiner should be directed to RuiMeng Hu whose telephone number is 571-270-1105. The examiner can normally be reached on Monday - Thursday, 8:00 a.m. - 5:00 p.m., EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edward Urban can be reached on 571-272-7899. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

RuiMeng Hu R.H./rh October 9, 2007

EDWARD F. URBAN
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600